


# AnyShop

The one that creates a new trend



# AnyShop is

a wall mountable Panel POS system with advanced features and powerful functions including internal stereo and camera. Equipped with camera, enables to secure against corruption by recording all transaction during the operation. AnyShop can be selectively equipped with Intel Atom, Intel Mobile or Intel core 2 duo processor. Designed with simple maintenance in mind, AnyShop's hard disk can be easily inserted or removed with one little touch by hand. Also, considerate I/O connection design allows device cables to be hidden inside the system base and therefore enhances the cable management. Its exclusive shape and unique selection of color enable the system completely match with any commercial areas.



### 1. Camera (option)

### 2. Customer Display

VFD or LCD type  
20 space columns x 2 lines

### 3. Dual monitor

12" 2nd LCD monitor  
1024 x 768 Resolution


### 4. Magnetic Stripe Reader (MSR) Smart Card Reader (SCR)

# What's Special




**AnyShop Any Space** Designed with user's requirement in mind, AnyShop provides a smart solution for any counter where space is premium. With its wall mounting fixture, AnyShop can be easily mounted in any location. The system will be an absolutely perfect solution for any daily and space saving required environment including hospitality, retail, entertainment, health care and other sectors.

**Powerful cooling system** The air came into the system to be completely discharged immediately after circulating CPU; the most heat generator and each effective system heat sink. Also the specialized duct system blocks any flow back heat to the system. With this smart cooling guarantee stable performance and long life span.



**Simplified maintenance** Removable slide-in HDD (screw-free)

**Different colors available** Just clip on/off to customize your POS



CPU(Support)		Intel Celeron Mobile 1.5GHz	Intel Core 2 Duo
Chipset		Intel 91x GME	Intel 945GME
HDD		SATA 2.5inch (Default 160GB)	
Memory		DDR2 SODIMM x 1 slot (Default 1GB up to 2GB)	DDR2 SODIMM x 2 slot (Default 1GB up to 4GB)
VGA		Intel 82915GM GMCH (Independent dual display)	Intel 82945GM GMCH (Independent dual display)
Display		15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution	
Internal I/O	USB	3 Ports (reserved for Touch controller, SCR EMV card, Camera, MSR controller)	
	PS/2	1 Keyboard with pin header	
	RS-232	COM 4 reserved for VFD	
		COM 5 & 6 with 9pin header	COM 3 with 9pin header
	D-SUB	Reserved for 2nd display	
	Extension	MINI PCI	
External I/O	LVDS	Main display use	
	Parallel	1 Port	
	USB	Rear 2, Side 2	
	PS/2	Mouse 1 / Keyboard 1	
	RS-232	COM 1 ~ 3 with +5/12V power output on 9pin	COM 1 ~ 2 with +5/12V power output on 9pin
	LAN	GbE LAN	
Options	Audio	Each 1 Line-out/ Line-in/ Mic	
	MSR	Comply with ISO 7811, Support 1 & 2, 2 & 3, 1& 2 & 3 track	
	SCR	EMV level	
	Camera	Camera	
	Dallas	Dallas I-button reader	
	VFD	VFD type customer display (20 x 2)	
	2nd LCD	12.1" LCD : 1024 x 768 resolution	
	DVR	DVR Card : 4channels support	
	WiFi	Mini PCI for wireless LAN	
VGA	Mini PCI for VGA card		
Qualification		CE, FCC, KCC	
Power Supply		AC 110 or 220V (Max.240 watt)	
OS Support		Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7	

\* Specifications are subject to change without prior notice





## The best price performance ratio, More affordable choice with Intel Atom processor

CPU(Support)		Dual-Core Intel ATOM 1.66GHz
Chipset		Intel ATOM NM10 express(Fanless)
HDD		SATA 2.5inch (Default 160GB)
Memory		DDR2 DIMM (Default 1GB to 4GB)
VGA		Intel Graphics Media Accelerator 3150
Display		15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution
Internal I/O	USB	4 Ports (3 ports reserved for Touch controller, SCR EMV card and MSR controller)
	Extension	MINI PCI
External I/O	Parallel	1 Port
	USB	Rear 3, Side 2
	PS/2	Mouse 1 / Keyboard 1
	RS-232	COM 1 ~ 2 COM 3 with +5/12V power output on 9pin
	LAN	GbE LAN
	Audio	Each 1 Line-out/ Line-in/ Mic
Options	MSR	Comply with ISO 7811, Support 1 & 2 , 2 & 3 , 1& 2 & 3 track
	SCR	EMV level
	Camera	Camera
	Dallas	Dallas I-button reader
	VFD	VFD type customer display (20 x 2)
Qualification		CE, KCC
Power Supply		AC 110 or 220V (Max.240 watt)
OS Support		Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7

\* Specifications are subject to change without prior notice



**POSBANK**® Co.,Ltd.

Room 805~808 New T Castle B/D, 429-1 Gasan-Dong, Geumcheon-Gu Seoul, Korea

Tel. +82-2-2626-9118 Fax. +82-2-2626-9119 E-MAIL Sales@posbank.com

www.posbank.com

Copyright(c) POSBANK Co.,Ltd. All rights reserved.